

MANKO 2135xpt SERIES 3 1/2" ARCHITECTURAL GRADE FIXED and HORIZONTAL SLIDING WINDOW SYSTEM STRUCTURAL PERFORMANCE AND CAPABILITIES

AAMA PERFORMANCE RESULTS

	AAMA Performance Rating	Air Infiltration @6.24psf	Water (psf)	Design Pressure	Structural Overload Pressure
Fixed	AW-PG100-F	≤ .1 cfm/ft ²	12.0psf	100psf	150psf
Horizontal Slider	AW-PG50-HS	≤ .3 cfm/ft ²	10.0psf	50psf	75psf

2135xpt Series Hardware Options

	Tandem Stainless Steel 3/4" Rollers	Field Adjustable Rollers	Stainless Steel Roller Track Cap	Integral Continuous Pull Handle	Head Mounted Limit Stops	Spring Loaded Automatic Jamb Locks	Single White Bronze Cam Actions Sweep Lock	Dual White Bronze Cam Actions Sweep Lock
XO/OX	S	S	O	S	O	S	O	O
XOX	S	S	O	S	O	S	O	O
S= Standard Hardware					O=Optional Hardware			

Sizing Capabilities for 2135xpt Series Windows (Frame Size)

	Width		Height		Max FT ²
	Min	Max	Min	Max	
Fixed	12	84	12	80	≤ 38
XO/OX	30	98	20	78	≤ 30
XOX	36	98	20	78	≤ 40

Glazing Infill Options

	1"	1 1/8"
Insulated	S	**O
**Hermetically sealed blind units are available		

Manko Window Systems Inc.
800 Hayes Drive
Manhattan, KS.
66502
PH: (800) 642 1488
FX: (800) 576 2656



Manko – Aurora, CO.
17500 E. 22nd Avenue
Aurora, CO. 80011
PH: (888) 642 1488
FAX: (303) 375 0669

Manko– Des Moines, IA.
3001 McKinley Avenue
Des Moines, IA. 50321
PH: (515) 288 7427
FAX: (515) 288 6968