



MANKO

WINDOW SYSTEMS INC.

www.mankowindows.com

2300i

TERRACE DOOR

Manko's heavy duty 2300i terrace door was designed with both performance and quality at the forefront. The door and frame are each thermally broken with a polyamide strut separating interior and exterior aluminum to maximize thermal performance. Glazing is structurally set at the factory for added quality control and a weather tight barrier. The 2300i door is constructed for durability by hydraulically crimping each of the four corners, with the frame being mechanically fastened together at each corner. Multipoint locking improves security and provides a tight seal from outside elements. Precision machined 3-way adjustable butt hinges allow for multi-directional adjustments with FRP bushings and stainless steel pins. The various operation configurations can adapt to your project requirements with options including single in-swing, single out-swing, or pair out-swing. Look no further, the 2300i terrace door can be the perfect fit for your next high performance entry system.



Features:

- ⇒ 4" frame depth, 2" door leaf depth
- ⇒ 1" — 1 3/16" glazing
- ⇒ 0.125" wall thickness
- ⇒ Dual weathering on door panels, frame and sill
- ⇒ Vertical and horizontal mid-rail options
- ⇒ Preglazed at factory for added quality control
- ⇒ Internal glass muntins available
- ⇒ Hermetically sealed blinds available
- ⇒ Interior snap trims available
- ⇒ Full range of anodized & AAMA 2605 painted finishes dual finish capability

