



MANKO

WINDOW SYSTEMS INC.

www.mankowindows.com

600

XO ■ XX ■ XOX ■ OXO ■ FIXED

Manko's 600 series horizontal sliding window system was designed for ventilation and value. The 600 series was originally marketed for hospitality projects, however its uses extend well beyond hospitality, including mixed use, office buildings, multi-family, and residences. This series' design includes pour and debridged thermally broken main frame and operable sash to provide improved thermal efficiency. Main frame and operable sash construction is mortise and tenon joinery with dual integral screw races. Marine wrap-around gasketing allows for a weather tight glazing seal. For added durability and extended operating life, the operable sash smoothly slides on tandem 3/4" steel rollers. If your project is seeking a quality, yet economical, sliding window, Manko's 600 series can be the perfect fit.

Performance Results:

- ⇒ AAMA — HS-C50
- ⇒ Air Infiltration — 0.28 CFM*
- ⇒ Water Resistance — 7.5 PSF*
- ⇒ System U-Value — 0.52
Using 0.35 COG U-Value

*Minimum gateway performance values listed, product meets or exceeds values



Features:

- ⇒ 3 1/4" overall frame depth
- ⇒ 7/8" insulated glass
- ⇒ Equal or unequal leg frames
- ⇒ Removable operating sashes
- ⇒ Dual finseal weathering on operating sashes
- ⇒ Preglazed at factory for added quality control
- ⇒ Extruded screen frames with aluminum screen wire
- ⇒ Exterior applied & between glass muntins available
- ⇒ Panning systems & interior snap trims available
- ⇒ Receptor systems available w/optional starter sill
- ⇒ Nailing fins available for efficient installation
- ⇒ Custom configurations with standard details available
- ⇒ Full range of anodized & AAMA 2605 painted finishes