

# MANKO 6035 SERIES 3 1/2" ARCHITECTURAL GRADE FIXED and HORIZONTAL SLIDING WINDOW SYSTEM STRUCTURAL PERFORMANCE AND CAPABILITIES

## AAMA PERFORMANCE RESULTS

	AAMA Performance Rating	Air Infiltration @6.24psf	Water (psf)	Design Pressure	Structural Overload Pressure
Fixed	AW-PG100-F	≤ .1 cfm/ft <sup>2</sup>	12.0psf	100psf	150psf
XX	CW-PG65-HS	≤ .3 cfm/ft <sup>2</sup>	10.0psf	65psf	97psf

## 6035 Series Hardware Options

	Tandem Stainless Steel 3/4" Rollers	Field Adjustable Rollers	Stainless Steel Roller Track Cap	Integral Continuous Pull Handle	Head Mounted Limit Stops	Spring Loaded Automatic Jamb Locks	Single White Bronze Cam Actions Sweep Lock	Dual White Bronze Cam Actions Sweep Lock
XX	S	S	O	S	O	S	O	O
XOX	S	S	O	S	O	S	O	O
S= Standard Hardware					O=Optional Hardware			

Sizing Capabilities for 6035 Series Windows (Frame Size)					
	Width		Height		Max FT <sup>2</sup>
	Min	Max	Min	Max	
Fixed	12	84	12	80	≤ 38
XX	30	98	20	78	≤ 30
XOX	36	98	20	78	≤ 40

Glazing Infill Options		
	3/4"	1"
Insulated	O	S*
*Hermetically sealed blind units are available		

Manko Window Systems Inc.  
800 Hayes Drive  
Manhattan, KS.  
66502  
PH: (800) 642 1488  
FX: (800) 576 2656



Manko – Aurora, CO.  
17500 E. 22<sup>nd</sup> Avenue  
Aurora, CO. 80011  
PH: (888) 642 1488  
FAX: (303) 375 0669

Manko– Des Moines, IA.  
3001 McKinley Avenue  
Des Moines, IA. 50321  
PH: (515) 288 7427  
FAX: (515) 288 6968