



MANKO

WINDOW SYSTEMS INC.

www.mankowindows.com

700

SINGLE HUNG ■ DOUBLE HUNG

Manko's 700 series single and double hung window system was designed for ventilation and value. The 700 series was originally marketed for mixed use projects, however its uses extend well beyond, including residence halls, office buildings, and multi-family. The 700 series' design includes pour and debridged thermally broken main frame and operable sash to provide improved thermal efficiency. Main frame and operable sash construction is mortise and tenon joinery with dual integral screw races. Marine wrap-around gasketing allows for a weather tight glazing seal. For added durability and extended operating life, the operable sash smoothly slides with either spiral or ultra-lift balances. If your project is seeking a quality hung window, Manko's 700 series can be the perfect fit.

Performance Results:

- ⇒ AAMA — H-C45
- ⇒ Air Infiltration — 0.06 CFM*
- ⇒ Water Resistance — 6.75 PSF*
- ⇒ System U-Value — 0.52
Using 0.35 COG U-Value

*Minimum gateway performance values listed, product meets or exceeds values

Features:

- ⇒ 3 1/4" overall depth
- ⇒ 7/8" insulated glass
- ⇒ Dual finseal weathering on operating sashes
- ⇒ Removable operating sashes
- ⇒ Preglazed at factory for added quality control
- ⇒ Extruded screen frames with aluminum screen wire
- ⇒ Exterior applied & between glass muntins available
- ⇒ Panning systems & interior snap trims available
- ⇒ Receptor systems available w/optional starter sill
- ⇒ Nailing fins available for efficient installation
- ⇒ Custom configurations with standard details available
- ⇒ Full range of anodized & AAMA 2605 painted finishes

